



SHOWA AC800

CUT LEVEL D

The new AC800 has a microporous nitrile with conductive filler, and embossed S-shaped palm finish.

18-gauge seamless knit with HPPE and conductive yarn.

Due to the nitrile coating with conductive carbon, these gloves are touch panel compatible.



BENEFITS

- Durable
- Robust grip
- Breathable
- Form-fitting
- Latex-free
- Abrasion-resistant
- Lightweight

INDUSTRIES



Aerospace



Airports & Ports



Automotive



Mechanical

FEATURES

- Embossed microporous nitrile coating
- Ergonomic
- Optimal liner design
- Silicone-free
- · Anti-static liner

HAZARDS



Cut



Antistatic

NORMS & CERTIFICATES

 ϵ

EN 388:2016

4X42D

EN 16350:2014

EN ISO 21420:2020





TRADES & APPLICATIONS

- Automotive repairs and maintenance
- Intricate parts handling
- Light assembly of oil-coated pieces
- · Mechanical and engineering
- Handling glass and windows

ANSI/ISEA 105-2016 CUT



Cut





PACKAGING

- Pair per polybag: 12
- Polybags per case: 6
- Pair per case: 72

LENGTH

220 - 270

COATING

Microporous nitrile

SIZES

6/S | 7/M | 8/L | 9/XL | 10/XXL

COLOUR

Grey

MATERIAL

- Engineered yarn
- Microfibre

USER INSTRUCTIONS

Gloves provide protection from chemical and mechanical hazards shown. Do not use gloves that show signs of wear. If required, cleanse outer surface of glove with running water. Discard used gloves in compliance with local regulations. Do not wear gloves when there is a risk of entanglement by moving parts of machines.

DISCLAIMER

The descriptions, characteristics, applications and photos are given for information purposes and do not constitute a contractual commitment. The manufacturer reserves the right to make any modifications it deems necessary.