



# **SHOWA XC510**

The new ultra-light XC510 combines 18-gauge UHMWPE liner providing cut-resistance level D/A4 with a durable, abrasive-resistant polyurethane palm coating usable in a wide variety of industrial applications.





## **BENEFITS**

- Cut-resistant
- Flexible
- Breathable
- Lightweight
- · Increased dexterity
- Seamless knit
- Form-fitting
- Abrasion-resistant

## **INDUSTRIES**



Mechanical



Automotive



Construction



Glass

## **FEATURES**

- HPPE reinforced
- Ergonomic
- Polyurethane palm coating

# **HAZARDS**



Cut

## **NORMS & CERTIFICATES**

EN 388:2016



4X42D

EN ISO 21420:2020



 $\widetilde{f i}$ 

ANSI/ISEA 105-2016 CUT

Cut

## **TRADES & APPLICATIONS**

- Light assembly of oil-coated pieces
- Maintenance
- Mechanical and engineering
- · Repair glass and windows
- Component Assembly





#### **PACKAGING**

- Pair per polybag: 12
- Polybags per case: 6
- Pair per case: 72

#### **COATING**

Polyurethane

#### **LINERS**

• Cut resistant - HPPE

## **SIZES**

6/S | 7/M | 8/L | 9/XL | 10/XXL

## **COLOUR**

Grey

#### **MATERIAL**

HPPE

# **USER INSTRUCTIONS**

Gloves provide protection from chemical and mechanical hazards shown. Do not use gloves that show signs of wear. If required, cleanse outer surface of glove with running water. Discard used gloves in compliance with local regulations. Do not wear gloves when there is a risk of entanglement by moving parts of machines.

## **DISCLAIMER**

The descriptions, characteristics, applications and photos are given for information purposes and do not constitute a contractual commitment. The manufacturer reserves the right to make any modifications it deems necessary.

