

SHOWA 874R

The SHOWA 874R chemical resistant glove offers superior protection against highly corrosive acids, ketones, and esters. Butyl rubber provides the highest permeation resistance to gases and water vapors of any material used to make gloves. A rough surface grip ensures optimum precision and increased durability.



BENEFITS

- Acid-resistant
- Impermeable
- Water-resistant

FEATURES

- Unlined
- Rolled Cuff
- Rough grip
- Unsupported
- Butyl rubber

NORMS & CERTIFICATES

Cat III



2777

EN 388:2016+A1:2018



0010X

EN ISO 374-1:2016+A1:2018/Type A



ABCIKLMNPST

EN ISO 374-5:2016



VIRUS



INDUSTRIES



Chemical



Mining

HAZARDS



Chemical

TRADES & APPLICATIONS

- Chemical spray and treatment
- Coating preparation
- Laboratory, pharma & analysis
- Painting & spray workshops
- Washing and cleaning
- Public utility
- Pipe Fitters
- Drilling
- Deck crew

GET IN TOUCH

SHOWA International | WTC - Tower 2 - Strawinskyalaan 1077 XX Amsterdam - The Netherlands

showagroup.com | info@showagroup.eu

© SHOWA GROUP 2024 | All rights reserved

PACKAGING

- Pair per polybag: 1
- Polybags per case: 12
- Pair per case: 12

THICKNESS

0.35 mm

LENGTH

350mm

COATING

- Butyl

LINERS

- Unlined

SIZES

7/S | 8/M | 9/L | 10/XL | 11/XXL

COLOUR

- Black

MATERIAL

- Unsupported

USER INSTRUCTIONS

Gloves provide protection from chemical and mechanical hazards shown. Do not use gloves that show signs of wear. If required, cleanse outer surface of glove with running water. Discard used gloves in compliance with local regulations. Do not wear gloves when there is a risk of entanglement by moving parts of machines.

DISCLAIMER

The descriptions, characteristics, applications and photos are given for information purposes and do not constitute a contractual commitment. The manufacturer reserves the right to make any modifications it deems necessary.

GET IN TOUCH

SHOWA International | WTC - Tower 2 - Strawinskyiaan 1077 XX Amsterdam - The Netherlands
showagroup.com | info@showagroup.eu
© SHOWA GROUP 2024 | All rights reserved